

2501/304      2508/304  
2502/304      2509/304  
2503/304

*DP III*

**FLUID MECHANICS AND THERMODYNAMICS**

Oct. / Nov. 2021

Time: 3 hours



**THE KENYA NATIONAL EXAMINATIONS COUNCIL**

**DIPLOMA IN MECHANICAL ENGINEERING  
(PRODUCTION, PLANT AND CONSTRUCTION PLANT OPTION)  
DIPLOMA IN AUTOMOTIVE ENGINEERING  
DIPLOMA IN WELDING AND FABRICATION**

**MODULE III**

**FLUID MECHANICS AND THERMODYNAMICS**

**3 hours**

**INSTRUCTIONS TO CANDIDATES**

*You should have the following for this examination:*

*Answer booklet;*

*Non programmable scientific Calculator;*

*Drawing instruments;*

*Tables of "Thermodynamics and Transport properties of fluids" by G.F.C Rogers and Y.R Mayhew.*

*This paper consists of TWO sections; A and B.*

*Answer FIVE questions in total taking TWO questions from section A and THREE questions from section B.*

*All questions carry equal marks.*

*Maximum marks for each question are indicated.*

*Candidates should answer the questions in English.*

**This paper consists of 5 printed pages.**

**Candidates should check the question paper to ascertain that all the pages are printed as indicated and that no questions are missing.**

## SECTION A: FLUID MECHANICS

Answer **TWO** questions from this section.

1. (a) Show that the average velocity of flow between parallel stationary plates is given by  $\bar{V} = \frac{Ph^2}{12\mu L}$ , where  $P$  is the pressure difference between the ends of the plates,  $h$  is the distance between the plates,  $L$  is the length of the plates and  $\mu$  is the fluid viscosity. (14 marks)

- (b) A horizontal pipe of 5 cm diameter conveys oil of dynamic viscosity 0.8 kg/ms. Measurements indicate a pressure drop of 20 kN/m<sup>2</sup> per meter of pipe length traversed. Determine the:

- (i) discharge of the oil through the pipe;  
(ii) velocity of the oil 1 cm from the pipe wall;  
(iii) shear stress at the wall of the pipe.

(6 marks)

2. (a) A pipe having a sudden enlargement in diameter from 300 mm to 450 mm is laid horizontally to connect two tanks of water. The smaller section of the pipe is 150 m long and the larger section is 210 m long. Water enters at the smaller end and exits at the larger end. The velocity of flow through the smaller section is 1.2 m/s. Take  $f = 0.006$  for the smaller section and 0.005 for the larger section.

- (i) Determine the loss of head at the:
- (I) entrance to the pipe;  
(II) enlargement;  
(III) exit to the second tank.
- (ii) Determine the difference in the levels of the water in the two tanks.

(10 marks)

- (b) A centrifugal pump having an impeller whose outer diameter is two times the inner diameter runs at 1000 rpm. The pump works against a total head of 40 m. The velocity of flow through the impeller is constant and equals to 2.5 m/s. The vanes are set back at an angle of 40° at outlet. If the outer diameter of the impeller is 500 mm and its width at outlet is 50 mm, determine the:

- (i) vane angle at inlet;  
(ii) work done by impeller on water per second;  
(iii) manometric efficiency.

(10 marks)

2501/304    2508/304  
2502/304    2509/304  
2503/304

3. (a) The thrust,  $P$  of a propeller depends upon the diameter  $D$ , speed of advance  $V$ , mass density  $\rho$ , speed of rotation  $N$ , and the coefficient of viscosity  $\mu$ .

$$\text{Show that } P = \rho D^2 V^3 \phi \left[ \frac{\rho V D}{\mu}, \frac{ND}{V} \right]$$

Where  $\phi$  means 'function of'.

(12 marks)

- (b) (i) Distinguish between geometric similarity and dynamic similarity.

(ii) The power  $P$  required to operate a test tunnel is given by  $P = \rho L^2 V^2 \phi \left( \frac{\rho V L}{\mu} \right)$

where  $\rho$  = density of fluid in which the test is done

$V$  = velocity of fluid

$L$  = length parameter

$\mu$  = dynamic viscosity

Tests are carried out on aerofoils in a laboratory to estimate the drag force on a 10 m long wing of an aircraft with a frontal projected area of 0.2 m by 10 m, which is subjected to a wind blowing at 20 m/s. One aerofoil is subjected to an airstream flowing at 40 m/s in a wind tunnel. The other aerofoil is subjected to a water stream flowing at 10 m/s. Determine the sizes of the aerofoils.

(8 marks)

### SECTION B: THERMODYNAMICS

Answer **THREE** questions from this section.

4. (a) With the aid of a diagram, explain the working principle of the Orsat apparatus used in the analysis of combustion gases. (8 marks)

- (b) A three stage, single acting reciprocating air compressor has a low pressure cylinder of 450 mm and 300 mm stroke. The clearance volume of the low pressure cylinder is 5% of the swept volume. The intake conditions are 1 bar and 18°C, while the delivery pressure is 15 bar. The intermediate pressure are ideal and the expansion and compression index is 1.3. Calculate the:

- intermediate pressures;
- effective swept volume of the low pressure cylinder;
- temperature and volume of air delivered per stroke at 15 bar;
- work done per kg of air.

(12 marks)

2501/304

2508/304

3

2502/304

2509/304

2503/304

Oct./Nov. 2021

Turn over

5. (a) A nozzle is a device for increasing the velocity of a steadily flowing stream of fluid. At the inlet to a certain nozzle, the enthalpy of the fluid is 3025 kJ/kg and the velocity is 60 m/s. At the exit from the nozzle, the enthalpy is 2790 kJ/kg. The nozzle is horizontal and there is negligible heat loss from it. Determine the:
- velocity at the nozzle outlet;
  - mass flow rate of the fluid, if the area at inlet is  $0.1 \text{ m}^2$  and the specific volume at inlet is  $0.19 \text{ m}^3/\text{kg}$ ;
  - exit area of the nozzle, if the specific volume at the nozzle exit is  $0.5 \text{ m}^3/\text{kg}$ .
- (6 marks)
- (b) The velocity of steam at inlet to a simple impulse turbine is 1000 m/s and the nozzle angle is  $25^\circ$ . The blade speed is 400 m/s. The blades are symmetrical and frictionless. Determine the:
- blade angle if the steam enters the blade without shock;
  - tangential force on the blade;
  - power developed for a mass flow rate of 0.75 kg/s.
- (14 marks)
6. (a) A boiler uses coal at the rate of 3300 kg/hr in producing steam with a specific enthalpy of 2850 kJ/kg from feed water with a specific enthalpy of 240 kJ/kg. The combustion of 1 kg of the coal produces 27000 kJ, of which 80% is useful in producing steam. Calculate the rate at which steam is produced. (6 marks)
- (b) A furnace wall consist of 130 mm wide refractory brick and 140 mm wide insulating firebrick separated by an air gap. The outside wall is covered with a 15 mm thickness of plaster. The inner surface of the wall is  $1400^\circ \text{C}$  and the room temperature is at  $30^\circ \text{C}$ . The heat transfer coefficient from the outside wall surface to the room is  $17 \text{ W/m}^2\text{K}$  and the resistance to heat flow of the air gap is  $0.18 \text{ K/W}$ . The thermal conductivities of the refractory brick, insulating firebrick and plaster are  $1.6 \text{ W/mK}$ ,  $0.3 \text{ W/mK}$  and  $0.14 \text{ W/mK}$ . Considering  $1 \text{ m}^2$  of surface area, determine the:
- rate of heat transfer;
  - interface temperatures;
  - temperature of the outside surface of the wall.
- (14 marks)

7. (a) (i) State the First law of thermodynamics. (5 marks)
- (ii) During a complete cycle of operation, a system is subjected to the following heat transfers; 800 kJ supplied and 350 kJ rejected. At two points, work is done by the system to the extent of 85 kJ and 35 kJ. At a third point, there is a further work transfer. Determine the amount of work done at this third point and state whether it is work done by or on the system.

(b) In a gas turbine unit, a high pressure (HP) stage turbine drives the compressor and a low pressure (LP) stage turbine drives the alternator. The overall pressure ratio is 7:1 and the maximum temperature is  $700^{\circ}\text{C}$ . The isentropic efficiencies of the compressor, HP turbine and L.P turbine are 0.8, 0.83 and 0.85 respectively. The mechanical efficiency of both shafts is 98%. Calculate the:

- (i) intermediate pressure between turbine stages when the intake conditions are 1.01 bar and  $25^{\circ}\text{C}$ ;
- (ii) thermal efficiency;
- (iii) shaft power for a mass flow rate of 60 kg/s.

Take: for air  $C_p = 1.005 \text{ kJ/kg K}$  and  $\gamma = 1.4$   
for gases  $C_p = 1.15 \text{ kJ/kg K}$  and  $\gamma = 1.33$

(15 marks)

**THIS IS THE LAST PRINTED PAGE.**